

Marley Antislip Plus

Detailed Description

Antislip Plus deck boards have been specifically designed to provide a durable and effective external antislip surface to minimise the risk of slipping, even in adverse weather conditions.

Available as a smooth or castellated profile with 2 resin based aggregate inserts injected into the grooves. Antislip Plus has been independently tested by the Health & Safety Laboratory using a Stanley Pendulum test in accordance with BS7976. Antislip Plus exceeds the minimum Pendulum Test Value (PTV) of 36.

Features & Benefits

- Available as a smooth or castellated profile
- Independently tested in accordance with BS 7976
- Antislip Plus® PTV values range from 63-78 (depending on wet or dry surface)
- Manufactured from sustainably sourced V quality European Redwood
- FSC or PEFC Certified
- Strength graded to C16 or C24 in accordance with BS 4978 by qualified graders
- BS 5268 and Eurocode span tables available
- Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life
- Naturewood treatment to Use Class 4
- Exterior Fire Retardant treatment to Euroclass B
- Low maintenance, no need for further preservative treatment
- TDCA DeckMark Plus performance rated product
- CE Marked

Marley recommends the use of Antislip Plus for: -

- Areas where there is public access
- Areas of high level pedestrian traffic
- Stairs and ramps

Product Guidance – As standard

Material

Kiln dried Vths quality European Redwood

Treatment

- Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life
- Preservative treated with Naturewood to Use Class 4 (in ground contact or fully submerged in fresh water)
- Fire Retardant treated to achieve Euroclass B

Fixing

Manufacturer recommends that Antislip Plus is fixed with 316 Grade Stainless Steel Deck Screws

Product Specification

Manufacturer

Name: Marley Limited
Address : Lichfield Road, Branston, Burton upon Trent, DE14 3HD
Website: www.marley.co.uk
E-mail : info@marley.co.uk
Tel : 01283 722588

Product Reference	Antislip Plus
Profile	Castellated Smooth
Grade	C16 C24
Finished Size	28 x 120mm 28 x 145mm 34 x 120mm 34 x 145mm 46 x 145mm 68 x 145mm
Length	3600mm 4200mm 4500mm 4800mm Precision end cutting service available – consult manufacturer
Inserts	2 GREY Bauxite inserts
Treatment	Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life Naturewood to Use Class 4 Fire Retardant treated to Euroclass B
Finish	End Coat to be applied to any cut surfaces
Fixings	316 Grade Stainless Steel Deck Screws – 10g x 63mm (28mm decking) 316 Grade Stainless Steel Deck Screws – 10g x 75mm (34mm decking) 316 Grade Stainless Steel Deck Screws – 12g x 100mm (46mm decking) 316 Grade Stainless Steel Deck Screws – 12g x 150mm (68mm decking)

Marley CitiDeck

Detailed Description

CitiDeck timber deck boards have been specifically designed to provide a durable and effective external antislip surface to minimise the risk of slipping, even in adverse weather conditions.

CitiDeck is a smooth profile with 2 white flint inserts injected into the deck board grooves. The smooth profile and slightly less inserts used in CitiDeck ensures it is an ideal product for the urban environment and inclusive access.

CitiDeck has been independently tested by the Health & Safety Laboratory using a Stanley Pendulum test in accordance with BS7976. Marley CitiDeck exceeds the minimum Pendulum Test Value (PTV) of 36.

Features & Benefits

- Smooth profiled boards
- Independently tested in accordance with BS 7976
- CitiDeck PTV values range from 61-73 (depending on wet or dry surface)
- Manufactured from sustainably sourced Vths quality European Redwood
- FSC and PEFC Certified
- Strength graded to C16 or C24 in accordance with BS 4978 by qualified graders
- BS 5268 and Eurocode span tables available
- Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life
- Naturewood treatment to Use Class 4
- Exterior Fire Retardant treatment to Euroclass B also available
- Low maintenance, no need for further preservative treatment
- Easy to keep clean as the smooth profile prevents accumulation of dirt and debris
- Less abrasive grit provides a more even surface for all users
- TDCA DeckMark Plus performance rated product
- CE Marked

Marley Eternit recommends the use of CitiDeck for: -

- Areas where there is public access
- Areas of high level pedestrian traffic
- Urban, inclusive environments
- Boardwalks, Bridges, Pubs, Restaurants, Schools, Offices, Retails
- Stairs and ramps

Product Guidance – As standard

Material

Kiln dried Vths quality European Redwood

Treatment

- Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life
- Preservative treated with Naturewood to Use Class 4 (in ground contact or fully submerged in fresh water)
- Fire Retardant treated to achieve Euroclass B

Fixing

Manufacturer recommends that CitiDeck is fixed with 316 Grade Stainless Steel Deck Screws

Product Specification

Manufacturer

Name: Marley Limited
Address : Lichfield Road, Branston, Burton upon Trent, DE14 3HD
Website: www.marley.co.uk
E-mail : info@marley.co.uk
Tel : 01283 722588

Product Reference	CitiDeck
Profile	Smooth
Grade	C16 C24
Finished Size	28 x 120mm 28 x 145mm 34 x 120mm 34 x 145mm 46 x 145mm 68 x 145mm
Length	3600mm 4200mm 4500mm 4800mm Precision end cutting service available – consult manufacturer
Inserts	2 WHITE flint inserts
Treatment	Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life Naturewood to Use Class 4 Fire Retardant treated to Euroclass B
Finish	End Coat to be applied to any cut surfaces

Fixings

- 316 Grade Stainless Steel Deck Screws – 10g x 63mm (28mm decking)
- 316 Grade Stainless Steel Deck Screws – 10g x 75mm (34mm decking)
- 316 Grade Stainless Steel Deck Screws – 12g x 100mm (46mm decking)
- 316 Grade Stainless Steel Deck Screws – 12g x 150mm (68mm decking)

Marley Standard

Detailed Description

Marley Standard deck boards are available in both castellated or smooth profiles suited for areas where an antislip surface may not be required or for matching with Antislip Plus or CitiDeck.

Features & Benefits

- Available as a smooth or castellated profile
- Manufactured from sustainably sourced V quality European Redwood
- FSC and PEFC Certified
- Strength graded to C16 or C24 in accordance with BS 4978 by qualified graders
- BS 5268 and Eurocode span tables available
- Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life
- Naturewood treatment to Use Class 4
- Exterior Fire Retardant treatment to Euroclass B also available
- Low maintenance, no need for further preservative treatment
- TDCA DeckMark performance rated product
- CE Marked

Product Guidance – As standard

Material

Kiln dried Vths quality European Redwood

Treatment

- Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life
- Preservative treated with Naturewood to Use Class 4 (in ground contact or fully submerged in fresh water)
- Fire Retardant treated to achieve Euroclass B

Fixing

Manufacturer recommends that Standard is fixed with 316 Grade Stainless Steel Deck Screws

Product Specification

Manufacturer

Name: Marley Eternit Limited
Address : Lichfield Road, Branston, Burton upon Trent, DE14 3HD
Website: www.marleyeternitdecking.co.uk
E-mail : info@marleyeternit.co.uk
Tel : 01283 722588

Product Reference	Standard
Profile	Castellated Smooth
Grade	C16 C24
Finished Size	28 x 120mm 28 x 145mm 34 x 120mm 34 x 145mm 46 x 145mm 68 x 145mm
Length	3600mm 4200mm 4500mm 4800mm Precision end cutting service available – consult manufacturer
Treatment	Preservative treated to Use Class 3 in accordance with BS 8417 to achieve a 30 year extended service life Naturewood to Use Class 4 Fire Retardant treated to Euroclass B
Finish	End Coat to be applied to any cut surfaces
Fixings	316 Grade Stainless Steel Deck Screws – 10g x 63mm (28mm decking) 316 Grade Stainless Steel Deck Screws – 10g x 75mm (34mm decking) 316 Grade Stainless Steel Deck Screws – 12g x 100mm (46mm decking) 316 Grade Stainless Steel Deck Screws – 12g x 150mm (68mm decking)