

Tile Design	
Minimum Pitch	
Maximum Pitch	
Size of Tile	
Minimum Headlap (Max Gauge)	
Tile Thickness	
Cover width	
Covering Capacity (net)	
Weight of Tiling	
Quantity Per Pallet	
Battens Required	
Recommended Batten Size	
Underlay	
Tile Colours Available	

--	--	--	--	--	--	--	--	--

Ventilation

Ventilation	
-------------	--

Base Layers

Underlay	
----------	--

Batten	
--------	--

Verge

Verge	
-------	--

Undercloak – Mortar Bedded	
----------------------------	--

Dry Verge	
-----------	--

Eaves

Eaves and Top Course	
----------------------	--

Abutment

Side Abutment

Top Edge Abutment

Ridges

Ridge - Dry Fix

Ridge - Mortar Bedded

Mono-Ridge

Hips and Valleys

Hip – Mortar Bedded

Hip – Dry Fix

Valley

Bonding Gutter

Fixings

Fixing

Clips

Nails

Other

Useful Links

Sustainability

Authority

British Standards

*Some product codes have been published, if you require a code which isn't present please contact our Technical Team on 01283 722230

** This publication is based on the latest data available at the time of printing. Due to product changes, improvements and other factors, the Company reserves the right to change or withdraw information contained herein without prior notice. For specific applications users should refer to the Technical Advisory Service and relevant Standards and Codes of Practice for guidance. The photography shown in the document should not necessarily be taken as recommendations of good practice. The printing process restricts the exact representation of colours. For true colour reference, please request product samples.

¹L TSA – Lead Sheet Training Academy